

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 21-Apr-15 01:46		FS — 10	BN 3726 SL 1548/ 3440/ 99	PJ: PN: HOPBAR	TG F2 — US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS 30.1 FR 20000 MB 30 DL -42 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1170		TS 12 B PD: 10132-075 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 UA 1000 UE 1022 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.1 FMX= 64 AMX= 120 EMX= 0.2 MEX= 125 FUP= 0.99			
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>10132</u> CALIBRATION FACTOR: <u>1170 %</u> PAK (*5000): _____ DATE: <u>24 APR 15</u> PDA OPERATOR: <u>Joe M. Wright</u>			
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		OP: laine lver:4.051 AT: PIEZOELECTRIC			

<-AT:PIEZORESISTIVE

OP: laine lver:4.051

AT:PIEZOELECTRIC->