

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 11-Apr-14 11:05		FS — 10	BN 882 SL 314/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- VS A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -39 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1135		TS 12 TB 8.0	B T1 9.3	PD: 10152-075 2L/C 4.7	VA 1000
				UE 1022	LP 0.00 ft LI 1.0

 contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	ACCEPT SQ-OFF FL-OFF PR-OFF VMX= 3.9 FMX= 61 AMX= 120 EMX= 0.2 MEX= 119 FVP= 0.99
	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 10152 CALIBRATION FACTOR: 1135 G/v PAK (*5000): DATE: 11-Apr-14 PDA OPERATOR: Erik Saff OP: erik [ver:4.08]
<-AT:PIEZORESISTIVE AT:PIEZOELECTRIC->	