

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics		FS —	BN 4246	PJ:	TG F2 -- US
13-Jan-16 23:53		10	SL 1858/ 3440/ 2	PN: HOPBAR	A2 F2 3.3
LE	39.6 ft				
AR	1.7 in2				
EM	30000 Ksi				
SP	0.492 K/ft3				
WS	16810 ft/s				
WC	16862 ft/s				
JC	0.40				
FM	1.00				
VM	1.00				
EA/C 30.3 Ks/ft					
UN KIPS±0.1					
FR 20000 MB 30					
DL	-41				
UT	-1				
PK	1 TM-PEAK				
F1	500				
F2	213				
A1	999				
A2	1145				
TS 12		B	PD: 10153-075	LP 0.00 ft	
TB 8.0		T1 9.6	2L/C 4.7	UA 1000	VE 1022 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.7 FMX= 72 AMX= 149
EMX= 0.3 MEX= 141 FVP= 0.99



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10153

CALIBRATION FACTOR: 1145%

PAK ←(×5000): DATE: 18 JAN 16

PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: laine lver:4.051

[AT:PIEZOELECTRIC->