

DPF

Pile Dynamics		FS	BN	PJ:	TG	F2	---	US
21-Apr-14 07:41		10	170	SL 133/ 3440/ 99	PN: HOPBAR	A2	F2	3.3
LE 39.6 ft								
AR 1.7 in2								
EM 30000 Ksi								
SP 0.492 K/ft3								
WS 16810 ft/s								
WC 16862 ft/s								
JC 0.40								
FM 1.00								
UM 1.00								
EA/C 30.3 Ks/ft								
UN KIPS*0.1								
FR 20000 MB 30								
DL -37								
UT -1								
PK 1 TM-PEAK								
F1 500								
F2 213								
A1 999								
A2 1125								
TS 12								
TB 8.0								
T1 9.4								
B PD: 10155-075								
2L/C 4.7								
VA 1000								
UE 1022								
LP 0.00 ft								
LI 1.0								
E1								
ACCEPT SQ-OFF FL-OFF PR-OFF								
UMX= 4.2								
FMX= 64								
AMX= 129								
EMX= 0.3								
MEX= 125								
FVP= 1.00								
ACCELEROMETER CALIBRATION		N.I.S.T. Traceable						
SERIAL NUMBER:		10155						
CALIBRATION FACTOR:		1125 G/v						
PAK (*5000):		DATE: 21-Apr-14						
PDA OPERATOR:		Erik S. [Signature]						
<-AT:PIEZORESISTIVE		OP: erik [ver: 4.05]						
AT:PIEZOELECTRIC-								

contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916