

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 20-May-14 04:42		FS — 10	BN 324 SL 154/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -37 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1130		TS 12 TB 8.0	B PD: 10162-075 T1 9.2 2L/C 4.7 UA 1000 UE 1022	LP 0.00 ft LI 1.0	
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 3.8 FMX= 59 AMX= 110 EMX= 0.2 MEX= 115 FVP= 1.01			
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable			
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		SERIAL NUMBER: 10162 CALIBRATION FACTOR: 1130 g/v PAK (*5000): DATE: 20-May-14 PDA OPERATOR: Erik Iver OP: erik [ver:4.05]			
<-AT:PIEZORESISTIVE		AT:PIEZOELECTRIC->			