

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 20-May-14 04:54	FS — 10	BN 356 SL 154/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30						
DL -42 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1150						
TS 12 TB 8.0					B PD: 10164-075 T1 9.3 2L/C 4.7 UA 1000	LP 0.00 ft LI 1.0
VE 1022						
ACCEPT SQ-OFF FL-OFF PR-OFF						

VMX= 4.0 FMX= 61 AMX= 120
EMX= 0.2 MEX= 119 FUP= 0.99

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10164

CALIBRATION FACTOR: 1150 G/v

PAK (*5000): DATE: 20-May-14

PDA OPERATOR: Erik S. J.

<-AT:PIEZORESISTIVE

OP: erik [ver:4.05]

[AT:PIEZOELECTRIC->

contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916