

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 20-May-14 04:34		FS — 10	BN 314 SL 154/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s							
JC 0.40 FM 1.00 UM 1.00							
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30							
DL -37 UT -1 PK 1 TM-PEAK							
F1 500 F2 213 A1 999 A2 1155		TS 12 TB 8.0	B T1 9.4	PD: 10165-075 2L/C 4.7	UA 1000 UE 1022	LP 0.00 ft LI 1.0	
ACCEPT SQ-OFF FL-OFF PR-OFF		UMX= 4.1 FMX= 64 AMX= 129 EMX= 0.2 MEX= 125 FUP= 1.01					
 contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 10165 CALIBRATION FACTOR: 1155 G/v PAK-(*5000)-: DATE: 20-May-14 PDA OPERATOR: <i>[Signature]</i> OP: erik [ver:4.05]					
<-AT:PIEZORESISTIVE		AT:PIEZOELECTRIC->					