

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 2019-05-30 08:01		FS — 10	BN 239 SL 557/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 17.0 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 7234 ft/s JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 90 DL -39 UT -1 IP 0.00 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1135		TS 12 B PD: 10166-075 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1024 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 5.1 FMX= 67 AMX= 159 EMX= 0.3 MEX= 131 FVP= 1.00			
ACCEPT 		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 10166 CALIBRATION FACTOR: 1135 %/V PAK (*5000): DATE: 30 MAY 19 PDA OPERATOR: <i>[Signature]</i>			
<-AT:PIEZORESISTIVE		OP: laine lver:5.011		AT:PIEZOELECTRIC->	