

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

|                                  |             |                 |                  |            |             |
|----------------------------------|-------------|-----------------|------------------|------------|-------------|
| Pile Dynamics<br>19-Jun-14 04:06 |             | FS —            | BN 1823          | PJ:        | TG F2 -- US |
|                                  |             | 10              | SL 413/ 3440/ 99 | PN: HOPBAR | A2 F2 3.3   |
| LE                               | 39.6 ft     |                 |                  |            |             |
| AR                               | 1.7 in2     |                 |                  |            |             |
| EM                               | 30000 Ksi   |                 |                  |            |             |
| SP                               | 0.492 K/ft3 |                 |                  |            |             |
| WS                               | 16810 ft/s  |                 |                  |            |             |
| WC                               | 16862 ft/s  |                 |                  |            |             |
|                                  |             |                 |                  |            |             |
|                                  |             |                 |                  |            |             |
|                                  |             |                 |                  |            |             |
|                                  |             |                 |                  |            |             |
| JC                               | 0.40        |                 |                  |            |             |
| FM                               | 1.00        |                 |                  |            |             |
| VM                               | 1.00        |                 |                  |            |             |
| EA/C 30.3 Ks/ft                  |             |                 |                  |            |             |
| UN KIPS*0.1                      |             |                 |                  |            |             |
| FR 20000 MB 30                   |             |                 |                  |            |             |
| DL -40                           |             |                 |                  |            |             |
| UT -1                            |             |                 |                  |            |             |
| PK 1 TM-PEAK                     |             |                 |                  |            |             |
| F1                               | 500         |                 |                  |            |             |
| F2                               | 213         |                 |                  |            |             |
| A1                               | 999         |                 |                  |            |             |
| A2                               | 1210        |                 |                  |            |             |
| TS 12                            |             | B PD: 10168-075 |                  | LP 0.00 ft |             |
| TB 8.0                           |             | T1 9.5          |                  | LI 1.0     |             |
|                                  |             | 2L/C 4.7        |                  | VA 1000    |             |
|                                  |             | VE 1022         |                  |            |             |

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA  
with your questions  
tel USA - 216 - 831- 6131  
fax USA - 216 - 831- 0916

VMX= 4.4 FMX= 69 AMX= 139  
EMX= 0.3 MEX= 135 FVP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10168

CALIBRATION FACTOR: 1210 %

PAK-(X5000): DATE: 19JUNE14

PDA OPERATOR: M. Wray

&lt;-AT:PIEZORESISTIVE

OP: laine tver:4:051

&gt;AT:PIEZOELECTRIC-&gt;