

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 23-Jun-14 03:33		FS — 10	BN 315 SL 163/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -39 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1145		TS 12 E B PD: 10171-075 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1022 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.1 FMX= 62 AMX= 129 EMX= 0.2 MEX= 121 FUP= 1.00			
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable			
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		SERIAL NUMBER: 10171 CALIBRATION FACTOR: 1145 G/V PAK (*3000): DATE: 23-Jun-14 PDA OPERATOR: Erik S.			
<-AT:PIEZORESISTIVE		OP: erik [ver:4.05]		AT:PIEZOELECTRIC->	